

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G01V 1/28	A2	(11) International Publication Number: WO 98/27444 (43) International Publication Date: 25 June 1998 (25.06.98)
(21) International Application Number: PCT/US97/24279 (22) International Filing Date: 18 December 1997 (18.12.97) (30) Priority Data: 08/770,209 19 December 1996 (19.12.96) US (71) Applicant: SCHLUMBERGER TECHNOLOGY CORPORATION [US/US]; 8311 North R.R. 620, Austin, TX 78720-0015 (US). (72) Inventor: CELNIKER, George, W.; 13114 Travis View Loop, Austin, TX 78732 (US). (74) Agents: SPEIGHT, Howard, L. et al.; Fish & Richardson P.C., Suite 1200, One Riverway, Houston, TX 77056 (US).		(81) Designated States: CA, NO, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>Without international search report and to be republished upon receipt of that report.</i>

(54) Title: **PERFORMING GEOSCIENCE INTERPRETATION WITH SIMULATED DATA**

(57) Abstract

A method, computer system, and computer program for analyzing geological data sampled from a subsurface region and an analysis of the geological data stored in a geoscience model on a magnetic media, including building a simulation input model from the geoscience model. A method, computer system, and computer program for analyzing geological data sampled from a subsurface region, the geological data and an analysis of the geological data being stored in a geoscience model on a magnetic media, including constructing a boundary for dividing the region into a first sub-region and a second sub-region; storing on the magnetic media the shape of the boundary as a parametric function whose parameter density can vary. A method, computer system, and computer program for analyzing geological data sampled from a subsurface region, the geological data and an analysis of the geological data being stored in a geoscience model on a magnetic media, including dividing the region into sub-regions, in each of which a material property varies without discontinuities.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

- 1 -

PERFORMING GEOSCIENCE INTERPRETATION WITH SIMULATED DATABackground

5 This invention relates to performing geoscience interpretation with simulated data.

 Geologists, geophysicists, petroleum engineers and production engineers use models, including computerized models, of the earth's shell to plan exploration and
10 production of hydrocarbons and, to a lesser extent, other minerals. As hydrocarbons become more and more scarce, the accuracy of the computerized models becomes increasingly important to limiting the cost of locating and producing hydrocarbons and the associated cost of
15 hydrocarbon products, such as gasoline and heating oil.

 Existing modeling systems use an "inversion" technique to model geoscience structures from acquired data. Acquired data, such as velocity measurements or data collected through seismic instrumentation, is
20 "inverted" and used to predict the location of subsurface structures and the physical properties of those subsurface structures.

 Once the inversion process produces predictions of the locations and physical properties of the subsurface
25 structures, they are modeled geometrically. Such models must be capable of representing complicated geometrical shapes, such as the shape of a salt dome or salt wall or the shape of a group of folded sedimentary beds.

 Commonly, modeling systems use a grid system to
30 represent subsurface structures. In a grid system, the subsurface structures are represented by points in space regularly spaced in the x-y plane and having a single value in the z plane. The values corresponding to those subsurface structures between the regularly-spaced points
35 are determined by interpolation. In a model for a large subsurface region, the number of points in space can be

- 2 -

numerous, requiring a great deal of storage, even if the subsurface structures are uniform in topography and physical properties across that space.

Another modeling system that has been applied to
5 the problem of modeling subsurface structures is constructional solid geometry ("CSG"). Under this approach, two or more solid primitives (such as cylinders or spheres) are combined to form a more complicated solid. The process begins with objects that are known to
10 be solid and adds or subtracts other solids to create new shapes. For example, subtracting a cylinder from a box will produce a box with a hole in it.

Summary

In general, in one aspect, the invention features
15 a method for analyzing geological data stored in a geoscience model on a magnetic media, comprising building a simulation input model from the geoscience model.

Implementations of the invention may include one or more of the following. The method may further
20 comprise acquiring data; interpreting the acquired data to produce the geoscience model; applying a simulator to the simulation input model to produce synthetic data; comparing the acquired data to the synthetic data to produce a difference; and editing the
25 geoscience model to reduce the difference. The simulator may comprise a simulation program used to develop acquisition equipment. Building the simulation model may comprise producing a finite element mesh. Building the simulation model may comprise producing a finite
30 difference grid. Building the simulation input model may comprise producing a tessellated model. The simulation input model may have a different format than the geoscience model.

In general, in another aspect, the invention
35 features a method for analyzing geological data

- 3 -

representing a subsurface region, the geological data being stored in a geoscience model on a magnetic media, comprising constructing a boundary for dividing the region into a first sub-region and a second sub-region;
5 storing on the magnetic media the shape of the boundary as a parametric function whose parameter density can vary.

In general, in another aspect, the invention features a method for analyzing geological data sampled
10 from a subsurface region, the geological data and an analysis of the geological data being stored in a geoscience model on a magnetic media, the method comprising dividing the region into sub-regions, in each of which a material property varies without
15 discontinuities.

Implementation of the invention may include one or more of the following. The method may further comprise describing the variation of the material property with a parametric function.

20 In general, in another aspect, the invention features a computer system for analyzing geological data stored in a geoscience model on a computer-readable magnetic media, comprising means for building a simulation input model from the geoscience model.

25 Implementations of the invention may include one or more of the following. The computer system may further comprise means for acquiring data; means for interpreting the acquired data to produce the geoscience model; means for applying a simulator to the simulation
30 input model to produce synthetic data; means for comparing the acquired data to the synthetic data to produce a difference; and means for editing the geoscience model to reduce the difference. The simulator may comprise a simulation program used to develop
35 acquisition equipment. The means for building the

- 4 -

simulation input model may comprise a means for producing a finite element mesh. The means for building the simulation data input model may comprise a means for producing a finite difference grid. The means for building the simulation input model may comprise a means for producing a tessellated model. The simulation input model may have a different format than the geoscience model.

In general, in another aspect, the invention features a computer system for analyzing geological data sampled from a subsurface region, the geological data and an analysis of the geological data being stored in a geoscience model on a computer-readable magnetic media, comprising means for constructing a boundary for dividing the region into a first sub-region and a second sub-region; means for storing on the magnetic media the shape of the boundary as a parametric function whose parameter density can vary.

In general, in another aspect, the invention features a computer system for analyzing geological data sampled from a subsurface region, the geological data and an analysis of the geological data being stored in a geoscience model on a magnetic media, the computer system comprising means for dividing the region into sub-regions, in each of which a material property varies without discontinuities.

In general, in another aspect, the invention features a computer program, residing on a computer-readable medium, for analyzing geological data sampled from a subsurface region and an analysis of the geological data stored in a geoscience model on a magnetic media, comprising instructions for causing a computer to build a simulation input model from the geoscience model.

- 5 -

Implementations of the invention may include one or more of the following. The computer program may further comprise instructions for causing the computer to acquire data; interpret the acquired data to produce the geoscience model; apply a simulator to the simulation input model to produce synthetic data; compare the acquired data to the synthetic data to produce a difference; and edit the geoscience model to reduce the difference. The simulator may comprise a simulation program used to develop acquisition equipment. The instructions which cause the computer to build the simulation input model may comprise instructions which cause the computer to produce a finite element mesh. The instructions which cause the computer to build the simulation input model may comprise instructions which cause the computer to produce a finite difference grid. The instructions which cause the computer to build the simulation input model may comprise instructions which cause the computer to produce a tessellated model. The simulation input model may have a different format than the geoscience model.

In general, in another aspect, the invention features a computer program, residing on a computer-readable medium, for analyzing geological data sampled from a subsurface region, the geological data and an analysis of the geological data being stored in a geoscience model on a magnetic media, comprising instructions for causing a computer to construct a boundary for dividing the region into a first sub-region and a second sub-region; store on the magnetic media the shape of the boundary as a parametric function whose parameter density can vary.

In general, in another aspect, the invention features a computer program, stored on a computer-readable medium, for analyzing geological data sampled

- 6 -

from a subsurface region, the geological data and an analysis of the geological data being stored in a geoscience model on a magnetic media, the computer program comprising instructions for causing a computer to
5 divide the region into sub-regions, in each of which a material property varies without discontinuities.

Description

Figs. 1-3 are block diagrams.

Figs. 4a-c, 5a-c and 6a-g are representations of
10 modeled items.

Simulation based interpretation ("SBI"), illustrated in Fig. 1, is an alternative to the inversion process for producing consistent models from acquired data. SBI begins by gathering acquired data 10 from the
15 geologic structures being modeled. The acquired data is interpreted and the resulting interpretation is captured as a geoscience model 12. The model is then tested by simulating an original acquisition experiment to produce synthetic data 14. For example, the simulation programs
20 used to develop acquisition equipment can be used to produce the synthetic data. Differences between the synthetic data 14 and the acquired data 10 are determined and used to adjust the model. Repeated iterations of these steps may cause the model to converge toward a
25 consistent model in which the differences between the synthetic and the acquired data are reduced. Making a single interpretation consistent with several measurements from a variety of experiments at one time continues to improve the quality of the interpretation.
30 Trained interpreters can use such a system interactively to build interpretations which can be relied upon for prediction purposes.

The geoscience model 12 is a permanent repository of the interpretation which is stored in a general format
35 so that input for a variety of simulators can be

- 7 -

generated from it. The geoscience model is editable so that interpreters can quickly converge the model to a consistent interpretation. Once the geoscience model exists and has been verified as consistent with existing
5 data, it can be used for a variety of predictive and planning purposes such as survey planning, estimating reservoir performance, and well completion planning.

The same technologies needed to support simulation based interpretation can be used to improve the process
10 for designing acquisition equipment. Equipment models placed within geoscience models may be used to build simulation input models for simulators. Simulation outputs are analyzed and compared to design specifications. Design alternatives and parameter
15 variations can be quickly tested and optimized prior to building the first prototype.

The same technologies needed to support simulation based interpretation can be used to improve the quality of acquired data by improving the process of survey
20 planning. Source and receiving equipment models placed in geoscience models may be used to generate simulation input models for simulators. Simulation outputs may be analyzed and used to optimize the placement of the sources and receivers.

25 One part of the geoscience model is a geometric representation of a portion of the earth's subsurface. In geoscience applications, known geometric primitives, such as spheres and cylinders, are less useful than in other applications. While the underground structures may
30 have started out their geological life capable of being described as simple geometric primitives, over time most have become distorted and are not easily represented using a grid system or a constructional solid geometry system. For example, if a set of sedimentary beds folds
35 over on top of itself, a single x-y point will have two

- 8 -

or more z values for a given bed. Further, the shapes are very complicated and not easily represented using CSG primitives.

The role of the geoscience model is to represent
5 the shape and properties of a system under study so that simulation programs may be used to enhance understanding of the system, as shown in Fig. 2. A variety of 3D modeling applications 20 including velocity modeling 22, borehole interpretation 24, seismic planning 26, and
10 others 28, share a common geoscience model 12. A simulation input model generator 30 generates from the geoscience model inputs required for a variety of simulators 32, such as migration 34, sonic 36, nuclear 38, electromagnetic 40 and other types of simulators 42.

15 A simulation input model uses the data format required by a simulation program. Each simulation program has its own specialized input data format. These formats are specified for a variety of reasons including, but not limited to, run time efficiency, data storage
20 efficiency, numerical methodology, and design history.

The current generation of simulation programs are based primarily upon the finite element, the finite difference, and ray tracing methods. The simulation input model generator provides automated procedures for
25 generating finite difference grids, finite element meshes and tessellated models for ray tracing that may be specialized to a particular simulation program's requirements.

The domain of the geoscience model is defined by
30 the simulation programs it is required to support. Despite the many different physical phenomena that the simulators model, they all have the following in common:

- (a) the continuum assumption;

- 9 -

- (b) a representation of distributed material properties;
- (c) a set of shared simulation techniques including the finite element, finite difference, and ray tracing methods.

The continuum assumption states that at a sufficiently large scale material properties, such as porosity and velocity, of a sub-region, which is a portion of a region, can be approximated by macroscopic properties that vary smoothly throughout the sub-region. The locations of discontinuities in the material properties, such as at a fault, are called "boundaries." Material property fields and their discontinuities can be represented in a geoscience model which contains the following information:

- (a) Shape, which is defined to be the location of the discontinuity boundaries;
- (b) Topology, which is defined to be the connections between boundaries and sub-regions;
- (c) Material properties, which are defined to be smoothly varying values within and on the boundaries of each sub-region and boundary object; and
- (d) Simulation input models, which are defined to be an extraction of the information in a geoscience model in a form suitable for use by a simulation package.

- 10 -

The geoscience model and the simulation input models are distinguished so that any number of simulation packages can be supported by a single geoscience model. The simulation input models support simulation based
5 interpretation applications.

Irregular space partition ("ISP") models are a representation of smoothly varying material property fields which may contain internal discontinuities that occur along distinct boundaries. A discontinuity in a
10 material property occurs where the material property value differs by a finite amount on either side of a discontinuity boundary. The location of the discontinuity boundaries make up the shape of the model. ISP models explicitly represent the shape of the
15 discontinuity boundaries. These boundaries may lie anywhere in an infinite space, have any shape, and intersect one another to partition space into sets of distinct sub-regions. Within any one sub-region, the material property can be represented by a smoothly
20 varying function.

The boundaries can be highly irregular in shape and can comprise portions where their shape is fairly uniform (such as a plane or a surface that approximates a plane) and other portions where the boundary is changing rapidly
25 (such as where folding occurs). The uniform portions of the boundaries can be represented accurately with fewer parameters. For example, a plane can be represented by three points. In the portions where the boundary is changing rapidly, however, it is necessary to use more
30 parameters to achieve an accurate representation.

For example, a "hybrid" surface may be made from both a grid and a mesh. The grid represents the bulk of the surface (typically the interior) where a high density of points is not necessary. The mesh represents the
35 surface boundary areas and surface intersections with

- 11 -

other surfaces, curves or points where high density is required. Thus, the surface is represented with a high density of parameters only where such a representation is necessary. This allows the system to store large
5 surfaces efficiently while maintaining higher accuracy of surface boundaries, when compared to regular grid representations.

ISP models are also used to model manufactured objects such as acquisition, drilling, and truck
10 equipment, which are represented as solid models. Points in a solid model are classified as being either in or out of the modeled object. In such cases, boundaries are not discontinuities between two regions but the demarcation of the end of the model. In a sense, there is nothing on
15 the other side of a boundary. Solid models do not contain internal boundaries.

A three-dimensional simulation-based application 50 includes three-dimensional modeling 52 which comprises four basic geoscience model building steps divided into
20 geometry modeling 54 and simulation input model generation 56, as shown in Fig. 3. The sequence of shape editing 58, topology model building 60, material property editing 62, and simulation input model generation 56 (which comprises finite element meshing/finite difference
25 gridding/tessellation for ray tracing) defines the scope of geoscience modeling.

As discussed above, a geoscience model may consist of a combination of a large number of simple geometry primitives. Each geometry primitive is initialized,
30 shaped, and positioned interactively by a user in relationship to the rest of the geoscience model. These geometry primitives include such shapes as lines, circles, planes, free-form surfaces, and solid sub-volumes.

- 12 -

The shape of a geometry primitive is defined to be the set of points it occupies in space. For example, a circle of radius R , lying in a plane parallel to the x - y plane and centered on the point $[a, b, c]$ is the set of
5 points given by the function

$$\begin{aligned}x &= a + R \cos (\text{theta}) \\y &= b + R \sin (\text{theta}) \\z &= c\end{aligned}$$

where theta is in the range $0 \leq \text{theta} < 2 \pi$.

10 These equations define a map from theta space to $[x, y, z]$ space; that is, for every value of theta there is a unique value of $[x, y, z]$. Since theta can be any of an infinite number of points the number of points in the circle is also infinite.

15 The values $\{a, b, c, R\}$ are called the parameters of the circle. Together, they completely specify all the points that define the circle. The functions which represent geometry primitive shapes are all parametric, single valued, continuous functions. These functions
20 have well behaved mathematical properties upon which the algorithms used to build, edit, and query complicated geoscience models depend. Parameterization allows an infinite number of points to be specified by a discrete number of values. Interfaces can be built that
25 conveniently allow the users to edit the parameter values. For example, a pick and drag window-based interface allows a user to select the circle's center point and drag it through space. The code that implements this behavior has only to convert the mouse's
30 position into a spatial (x, y, z) location and use those values to change the shape of the circle, e.g. $a = x$, $b = y$, $c = z$.

Shape editing is the interactive process of modifying a shape's parameters until it is in a form
35 suitable for use with the rest of the geoscience model.

- 13 -

In the circle example, the object has only 4 parameters. In general, an object may have many more parameters. For example, a free-form surface represented as a triangulated mesh can have thousands of parameters. The application which helps a user edit the shape of an object with a large number of parameters may very well be a complicated application in itself. But all shape editing applications are dedicated to creating new geometry primitives and setting their parameter values.

10 There are two kinds of shape editing applications: those that extract shapes from data, and those that build shapes from scratch. Extracting shape from data is a user directed semi-automated process, while building shape definitions from scratch is interactive.

15 ISP and solid models are built by combining sets of geometry primitives and recording where the primitives intersect one another. In three-dimensional ISP building, a user creates a number of surface boundary shapes and uses them to sub-divide space locally to define a set of sub-volumes in a single model. Where boundaries intersect one another, new intersection geometry objects are created to represent the intersection shape and to record the connection among the boundaries. When sets of boundaries interact to separate one region of space from another, a sub-region object is created for each distinct sub-region. Groups of sub-regions may be used to represent application features such as formations and invasion zones, and boundaries may be used to represent application features like horizons, faults, and borehole boundaries. Not every object in a geoscience model is used to represent an application feature, but every application feature with a geometric description is associated with a geometry object. Geometry objects representing the shape of an application feature are called geometry features.

35

- 14 -

Building solid models is very similar to building ISP models. In solid modeling, the user builds a sequence of solid shapes and combines them together with the standard boolean operators of union, subtract, and intersect to create accurate representations of complicated machined metal solids. The side effect of editing the topology structure representation when combining primitives into ISP and solid models is automated. Sequences for building ISP and solid models may use the subdivide, insert, and subtract operators, which are just a few of the topology editing operators to be found in a general geometry modeling application and which are described in detail in co-pending application serial number _____, entitled "Modeling Geological Structures and Properties," incorporated by reference.

An example of ISP modeling is shown in Figs. 4a-c. A volume 70 may be subdivided by two surfaces 72 and 74, as shown in Fig. 4a. Another volume 76, representing, for example, a salt dome, may be inserted into the subdivided volume 78 as shown in Fig. 4b. The result is a subdivided volume 80 containing a variety of complicated shapes, as shown in Fig. 4c. An analyst can mark interesting geometry objects such as the horizons, formed by surfaces 72 and 74, or the salt body 76.

An example of solid model building is illustrated Figs. 5a through 5c. A series of sub-volumes 82a-d is subtracted from an initial shape 84, as shown in Fig. 5a to produce the volume 86, illustrated in Fig. 5b. Additional sub-volumes 88a-c are subtracted from the volume, as shown in Fig. 5B, resulting in a sub-volume 90, shown in Fig. 5C.

Material property editing is the process of annotating a geoscience model with material properties. Material property fields, like shape, are represented by

- 15 -

functions. A parametric function is used to map each point in a modeling image space to a material property value. Any continuous function may be used. Some of the more common functions include: constants, constant
5 gradients, and free-form functions (such as triangulated surfaces, poly-lines, NURBS, bi-cubic patches, etc.).

The shape and topology information in a geoscience model is used to model material property discontinuities. Each material property discontinuity is marked by a
10 geometry boundary creating sets of sub-regions in which the material property field is smoothly varying. Each sub-region is associated with its own function for representing a common material property field. Thus,
15 using different material functions on either side of a discontinuity boundary. It takes two steps to evaluate the material property at a point within a geoscience model:

- 20 (a) find the sub-region containing the point and its associated material property function; and
- (b) evaluate the sub-region's material property function at the required point.

Any number of material property fields can be represented in a geoscience model by storing one parametric function
25 for each material property in each sub-region.

Material property fields may also be defined on region boundaries. These are known as "boundary material properties" as opposed to "region material properties." Boundary material properties can be associated with the
30 entire boundary or with just one side of the boundary. Oriented boundary material properties may be used to describe boundary value problems.

- 16 -

The value of a material property at a point is a tensor. The tensor may be represented by either a scalar, vector, or matrix quantity. It is a description of properties with intrinsic geometric properties, e.g., it remains invariant under coordinate transformations. The components of a tensor are represented in a chosen coordinate system. Changing the coordinate system changes the values of the coordinates. Relationships between tensor quantities as defined by fundamental physical laws are independent of coordinate transformations. For example, Newton's law defines the relationship between acceleration, A , and force, F , as, $F = mA$, which defines the quantity mass, m . This relationship is true independent of which coordinate system is chosen to describe the components of the tensor quantities F , m , and A . In this system, there is no special accommodation for tensors. The components of a high order tensor are stored as a set of scalar values and the applications manage the constraints between component values.

Material property editing, like shape editing, occurs in two ways: building material property fields from data and from scratch. Material property editing consists of:

- (a) Specifying the set of material properties to be represented in the geoscience model.
- (b) Selecting and assigning a parametric function for each material property in each sub-region, and optionally in each boundary, and on each side of a boundary.

- 17 -

- (c) Editing the parameters of the material property parametric functions as desired.

Representing a material property field in an ISP geoscience model is done by using functions. Functions
5 are used to represent the boundary shapes which mark the discontinuities within the material property field and map points from a parameter space to a shared image space. Each boundary has its own parameter space but all boundaries share a common image space. The parameter
10 space is the domain of the shape function and the shared image space is its range. The shared image space is used as the domain for a function which represents a material property field. Every point in the shared image space is projected into a material property value by the material
15 property function.

The steps used to subdivide a volume and assign material properties to the volume are illustrated in Figs. 6a-g. A first horizon 100 is represented in parameter space, as shown in Fig. 6a. A function, f_1 , 102,
20 provides a mapping from parameter space to region space. The representation 104 of the horizon in region space is shown in Fig. 6b. Similarly, a second horizon 106 is represented in parameter space as shown in Fig. 6c. A function, f_2 , 108, provides a mapping from parameter space
25 to region space. The representation 110 of the horizon in region space is shown in Fig. 6d. The subdivision of the region by the first horizon 104 and the second horizon 110 forms three subregions 112, 114, 116, as shown in Fig. 6e. Region 112 is the subregion below
30 horizon 110. Region 114 is the region between the two horizons, and region 116 is the region above horizon 104. A material property, MP, is assigned a value represented by the function MP_1 , 118 in region 112. The material property is assigned a different function, MP_2 , 120, in

- 18 -

region 114. A representation of the value of MP 122 in region 112 is shown in Fig. 6f. A representation of material property MP 124 in region 114 is shown in Fig. 6g.

5 The process of simulation input model generation consists of an interactive phase in which the user specifies the size, location, and properties of a mesh or grid to be stored in a simulation input model description. The interactive phase is followed by an
10 automated phase in which the simulation input model is built given the geoscience model and simulation input model description.

 The invention may be implemented in hardware or software, or a combination of both. However, preferably,
15 the invention is implemented in computer programs executing on programmable computers each comprising a processor, a data storage system (including volatile and non-volatile memory and/or storage elements), at least one input device, and at least one output device.
20 Program code is applied to input data to perform the functions described above and generate output information. The output information is applied to one or more output devices, in known fashion.

 Each program is preferably implemented in a high
25 level procedural or object oriented programming language (such as C++ or C) to communicate with a computer system. However, the programs can be implemented in assembly or machine language, if desired. In any case, the language may be a compiled or an interpreted language.

30 Each such computer program is preferably stored on a storage media or device (e.g., ROM or magnetic/optical disk or diskette) readable by a general or special purpose programmable computer, for configuring and
operating the computer when the storage media or device
35 is read by the computer to perform the procedures

- 19 -

described herein. The inventive system may also be considered to be implemented as a computer-readable storage medium, configured with a computer program, where the storage medium so configured causes a computer to
5 operate in a specific and predefined manner to perform the functions described herein.

Other embodiments are within the scope of the following claims.

What is claimed is:

- 20 -

1. A method for analyzing geological data sampled from a subsurface region and an analysis of the geological data being stored in a geoscience model on a magnetic media, comprising
 - 5 building a simulation input model from the geoscience model.
 2. The method of claim 1, further comprising acquiring data; interpreting the acquired data to produce the
10 geoscience model; applying a simulator to the simulation input model to produce synthetic data; comparing the acquired data to the synthetic data to produce a difference; and
15 editing the geoscience model to reduce the difference.
 3. The method of claim 2 wherein the simulator comprises a simulation program used to develop acquisition equipment.
 - 20 4. The method of claim 1, wherein building the simulation input model comprises producing a finite element mesh.
 5. The method of claim 1, wherein building the simulation input model comprises producing a finite
25 difference grid.
 6. The method of claim 1, wherein building the simulation input model comprises producing a tessellated model.
 7. The method of claim 1, wherein the simulation
30 input model has a different format than the geoscience model.
 8. A method for analyzing geological data sampled from a subsurface region, the geological data and an analysis of the geological data being stored in a
35 geoscience model on a magnetic media, comprising

- 21 -

constructing a boundary for dividing the region into a first sub-region and a second sub-region;

storing on the magnetic media the shape of the boundary as a parametric function whose parameter density
5 can vary.

9. A method for analyzing geological data sampled from a subsurface region, the geological data and an analysis of the geological data being stored in a geoscience model on a magnetic media, the method
10 comprising

dividing the region into sub-regions, in each of which a material property varies without discontinuities.

10. The method of claim 9, further comprising describing the variation of the material property with a
15 parametric function.

11. A computer system for analyzing geological data stored in a geoscience model on a computer-readable magnetic media, comprising

means for building a simulation input model from the
20 geoscience model.

12. The computer system of claim 11, further comprising

means for acquiring data;
means for interpreting the acquired data to produce
25 the geoscience model;

means for applying a simulator to the simulation input model to produce synthetic data;

means for comparing the acquired data to the synthetic data to produce a difference; and

30 means for editing the geoscience model to reduce the difference.

13. The computer system of claim 12 wherein the simulator comprises a simulation program used to develop acquisition equipment.

- 22 -

14. The computer system of claim 11, wherein the means for building the simulation model comprises a means for producing a finite element mesh.

15. The computer system of claim 11, wherein the
5 means for building the simulation model comprises a means for producing a finite difference grid.

16. The computer system of claim 11, wherein the means for building the simulated model comprises a means for producing a tessellated model.

10 17. The computer system of claim 11, wherein the simulation input model has a different format than the geoscience model.

18. A computer system for analyzing geological data sampled from a subsurface region, the geological data and
15 an analysis of the geological data being stored in a geoscience model on a computer-readable magnetic media, comprising

means for constructing a boundary for dividing the region into a first sub-region and a second sub-region;

20 means for storing on the magnetic media the shape of the boundary as a parametric function whose parameter density can vary.

19. A computer system for analyzing geological data sampled from a subsurface region and an analysis of the
25 geological data, the geological data being stored in a geoscience model on a magnetic media, the computer system comprising

means for dividing the region into sub-regions, in each of which a material property varies without

30 discontinuities.

20. A computer program, residing on a computer-readable medium, for analyzing geological data sampled from a subsurface region, the geological data and an analysis of the geological data being stored in a

- 23 -

geoscience model on a magnetic media, comprising instructions for causing a computer to

build a simulation input model from the geoscience model.

5 21. The computer program of claim 20, further comprising instructions for causing the computer to acquire data;

interpret the acquired data to produce the geoscience model;

10 apply a simulator to the simulation input model to produce synthetic data;

compare the acquired data to the synthetic data to produce a difference; and

edit the geoscience model to reduce the difference.

15 22. The computer program of claim 21 wherein the simulator comprises a simulation program used to develop acquisition equipment.

23. The computer program of claim 20, wherein the instructions which cause the computer to build the
20 simulation input model comprise instructions which cause the computer to produce a finite element mesh.

24. The computer program of claim 20, wherein the instructions which cause the computer to build the simulation input model comprise instructions which cause
25 the computer to produce a finite difference grid.

25. The computer program of claim 20, wherein the instructions which cause the computer to build the simulation input model comprise instructions which cause the computer to produce a tessellated model.

30 26. The computer program of claim 20, wherein the simulation input model has a different format than the geoscience model.

27. A computer program, residing on a computer-readable medium, for analyzing geological data sampled
35 from a subsurface region, the geological data and an

- 24 -


analysis of the geological data being stored in a geoscience model on a magnetic media, comprising instructions for causing a computer to

construct a boundary for dividing the region into a
5 first sub-region and a second sub-region;

store on the magnetic media the shape of the boundary as a parametric function whose parameter density can vary.

28. A computer program, stored on a computer-
10 readable medium, for analyzing geological data sampled from a subsurface region, the geological data and an analysis of the geological data being stored in a geoscience model on a magnetic media, the computer program comprising instructions for causing a computer to
15 divide the region into sub-regions, in each of which a material property varies without discontinuities.

1/5

**Figure 1**

2/5





Figure 2

3/5

**Figure 3**

4/5




Figure 4A




Figure 5A




Figure 4B




Figure 5B




Figure 4C




Figure 5C

5/5




Figure 6A




Figure 6C




Figure 6B





Figure 6D

Figure 6E



$MP=MP_1([x,y,z])$ 118

$MP=MP_2([x,y,z])$ 120




Figure 6F




Figure 6G

